



## Lucci Connect City LED Recessed CCT 92mm Cut Out Downlight in White

SKU: 170622

### Details

The Lucci Connect City Downlight has all the features of a smart globe but in a downlight form and allows you to choose between a range of 2700K Warm White through to 6500K Daylight. Lucci Connect City Downlights are Wi-Fi enabled and work off the Lucci Connect App. This app allows you to control your lighting like never before. Set the mood by selecting from a spectrum of colours, dim to create ambience, and customise a lighting network specific to you. Set up and control is simple with the easy to use Lucci Connect app. A Lucci Connect Gateway will be required in conjunction with the App to control your lights remotely. Combine with a smart home hub to enable voice control access and immerse yourself in the ultimate lighting experience. The Lucci Connect App can be downloaded from both the Google Play and Apple App stores.

### Specifications

|                               |                |
|-------------------------------|----------------|
| SKU                           | 170622         |
| Colour/Finish                 | White          |
| Dimmable                      | Via APP        |
| Ip Rating                     | IP20           |
| Globe Type                    | Integrated LED |
| Globe Quantity                | 0              |
| Wattage Max                   | 11W            |
| Kelvins                       | 2200K-6500K    |
| Lumens                        | 700            |
| CRI                           | >90            |
| Efficacy                      | 63.6           |
| Beam Angle                    | 60 degrees     |
| Field Angle                   | 100 degrees    |
| Average Rated Life            | 25,000 hours   |
| Cut Out Size (mm)             | 92             |
| Ic (Insulation Contact) Rated | IC-4           |

|                       |                           |
|-----------------------|---------------------------|
| Colour Temperature    | Warm White - Day Light    |
| Material              | Aluminium                 |
| Voltage               | 240V                      |
| Surge Protection      | 500V                      |
| Double Insulated      | true                      |
| Sdcm                  | =6                        |
| Operating Temperature | -20 degrees to 40 degrees |
| Ambient Temperature   | 25 degrees                |
| Warranty              | 2 years                   |
| Brand                 | Lucci Connect             |
| Style                 | Modern                    |