



## Vivid LED Recessed Colour Switch 90mm Cut Out Downlight in White

SKU: 170571

### Details

The LEDlux Vivid colour switch downlight enable you to choose which colour tempertaure of light you would like between 3000K Warm White - 4000K Cool White and 5000K Daylight. This light is IP44 rated only after it is fully installed and this must be maintained during installation. however the driver and back of the light is IP20 rated. This downlight is compatible with the following dimmers:

Iumex Load Smart LT1D450Is;

DIGINET LED Smart MEDM;

Clipsal 31E2RUDM, 32E450TM, 32E450UDM, 31E2PUDM and 32ELEDM;

HPM: Cat. 4007;

LUCCI LEDlux SKU#290998, SKU #290997

It is highly recommended to use the LUCCI LEDlux dimmers for best dimming range.



### Specifications

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SKU                 | 170571                                                                                                                                                                   |
| Colour/Finish       | White                                                                                                                                                                    |
| Dimmable            | Yes                                                                                                                                                                      |
| Recommended Dimmers | Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018. |
| Ip Rating           | IP44                                                                                                                                                                     |
| Globe Type          | Integrated LED                                                                                                                                                           |
| Globe Quantity      | 0                                                                                                                                                                        |
| Wattage Max         | 10.5W                                                                                                                                                                    |
| Kelvins             | 3000K/4000K/5000K                                                                                                                                                        |
| Lumens              | 1000                                                                                                                                                                     |
| CRI                 | >80                                                                                                                                                                      |



|                               |                                 |
|-------------------------------|---------------------------------|
| Efficacy                      | 95.2                            |
| Beam Angle                    | 110 degrees                     |
| Field Angle                   | 160 degrees                     |
| Average Rated Life            | 25,000 hours                    |
| Cut Out Size (mm)             | 90                              |
| Ic (Insulation Contact) Rated | IC-4                            |
| Colour Temperature            | Warm White/Cool White/Day Light |
| Material                      | Aluminium                       |
| Voltage                       | 240V                            |
| Surge Protection              | 500V                            |
| Double Insulated              | true                            |
| Sdcm                          | =6 (3000K/5000K) =7 (4000K)     |
| Operating Temperature         | -20 degrees to 40 degrees       |
| Ambient Temperature           | 50 degrees                      |
| Warranty                      | 5 years                         |
| Brand                         | Lucci                           |
| Style                         | Modern                          |
| Down Lighting Type            | SMD LED                         |
| Downlight Technology          | Scene Change via Toggle         |